

Technical Specifications

MODEL	SLVP-500	SLVP-600	SLVP-1000	SLVP-1500
Rated Power	500W	600W	1000W	1500W
Peak Power	1000W	1200W	2000W	3000W
Input Voltage	DC 12V			
Output Voltage	AC 220 V			
Output Frequency	50/60Hz			
No-load current	<0.42A	<0.44A	<0.57A	<0.63A
Waveform	Pure Sine Wave (THD<3%) at rated input voltage			
Voltage Range	10.8V-15.5V(12V version)			
Efficiency	More than %85			
Protection	Battery Low Alarm,Battery Low Shutdown,Battery Polarity Reverse by Fuse			
Battery Types	Open & sealed lead acid battery			
Certification	CE-EMC/LVD,ROHS/REACH/IATF16949			
Cooling fan	By load and temperature control			
USB port	5V,2.1A			

MODEL	SLVP-2000	SLVP-2500	SLVP-3000	SLVP-4000
Rated Power	2000W	2500W	3000W	4000W
Peak Power	4000W	5000W	6000W	8000W
Input Voltage	DC 12V			
Output Voltage	AC 220 V			
Output Frequency	50/60Hz			
No-load current	<0.67A	<0.73A	<0.81A	<0.92A
Waveform	Pure Sine Wave (THD<3%) at rated input voltage			
Voltage Range	10.8V-15.5V(12V version)			
Efficiency	More than %85			
Protection	Battery Low Alarm,Battery Low Shutdown,Battery Polarity Reverse by Fuse			
Battery Types	Open & sealed lead acid battery			
Certification	CE-EMC/LVD,ROHS/REACH/IATF16949			
Cooling fan	By load and temperature control			
USB port	5V,2.1A			